



Radio Society of Great Britain

Advancing amateur radio since 1913



RSGB 2025 Band Plan

QuickLinks:-

Updated: January-2025

[Recent Changes](#)

[2019 Changes](#)

[Older Changes](#)

[Notes](#)

[LF](#)

[MF](#)

[HF](#)

[VHF](#)

[UHF](#)

[Microwave](#)

[mmWave](#)

NB: These band plans are largely based on those agreed at IARU Region-1 General Conferences with some local differences on frequencies above 430 MHz.

© 2025 Radio Society of Great Britain - all rights reserved

Date	Description
2020	
11-Dec-2019	60m: Editorial - Added hyperlink for 5MHz guidance page
7-Dec-2019	70cm: Removal of BW limits in 430-431.9, 433.6-434.0, 435-440 to facilitate new digital mode
7-Dec-2019	70cm: Added General Note re FM/DV bandwidth
7-Dec-2019	70cm: Removal of CW-only EME centre. 432.0-432.1 now more generic CW/MGA
9-Dec-2019	23cm: Deleted PSK31 CoA at 1296.138
9-Dec-2019	23cm: Deleted redundant Notes 3 & 4
11-Dec-2019	2mm: Added information note re NoV access to frequencies >275 GHz by Full Licensee
9-Dec-2019	Notes Page: Added CoA definition
9-Dec-2019	Notes Page: SSB usage guidance editorial update to 7053 from 704;
11-Dec-2019	Notes Page: Updated NoV bands reference to include 71 MHz and >275 GHz
2021	
2-Dec-2020	15M: Added Note-1 for non-exclusive satellite usage designation in 21.125 - 21.14
2-Dec-2020	10M: Removal of Maximum Bandwidth limits in 29.000-29.510 to facilitate wideband experimentation
2-Dec-2020	10M: Added Note-1 regarding experimental wideband operation
2-Dec-2020	6M: Split of the 50.500-52 MHz range into more specific IARU-aligned segments
2-Dec-2020	6M: Deletion of 50.510 SSTV and 50.550 MHz Image designations
2-Dec-2020	6M: Gateways now FMDV (and shorter description as not all are on common IARU channel)
2-Dec-2020	6M: Deletion of IARU Repeater Outputs at 51.9 MHz - not used in the UK
2-Dec-2020	6M: Editorial update to Note-2
2-Dec-2020	6M: Typo fixed - removed duplicate Note-5 (Excel only)
4-Dec-2020	6M: Note-5 usage - 50.770/790 designation moved to 51.970/990
4-Dec-2020	6M: Wideband experimentation Note-6 updated in line with new IARU band plan
2-Dec-2020	4M: 70.25 Meteor Scatter and 70.20 SSB updated from calling to centre
2-Dec-2020	2M: Deletion of Note-7 re older EME range of 144.110-144.160 (to align with 144.100-144.150 band edge)
2-Dec-2020	2M: Deleted 144.200 MHz Random MS SSB
4-Dec-2020	70cm: 432.370 MHz FSK441 calling renamed to Meteor Scatter calling
4-Dec-2020	70cm: Removal of Fast Scan (Analogue) TV and Note-4 that related to
4-Dec-2020	70cm: Split of 435-438 MHz to more clearly designate Satellite and Wideband experimentation
4-Dec-2020	13cm: Removal of 500 Hz subsection to simplify the 2320.00-2323.800 narrowband segment
4-Dec-2020	9cm: Editorials - correction of narrowband segment to be 3400-3400.8 and former EU17 note remove
9-Dec-2020	Notes: Shortened 28 MHz
9-Dec-2020	Notes: Shortened 3.5 MHz
9-Dec-2020	Notes: Added new Transmitter Setup and Linearity general note
2022	
17-Dec-2021	136kHz: Updated RR footnote to remove Iran as per WRC-19 outcome
17-Dec-2021	50MHz: Correct Experimental Bandwidth in RadCom edition (Excel master corrected)
17-Dec-2021	144MHz: Extra Internet Gateway designations added at on former packet channel
12-Jan-2022	Excel master editorials - now has frequency-based tabs, instead of wavelength
12-Jan-2022	Excel master editorials - added year header to older years change note
2023	
21-Dec-2022	No formal changes for Jan-2023, but please note the following are under review
21-Dec-2022	a) HF: IARU review / expansion of data segment
21-Dec-2022	b) 145MHz: Repeater usage / spectrum efficiency (inc Note-11)
23-Dec-2022	c) Implications of WRC-23 on 50 MHz, 1.3GHz and perhaps other band
23-Dec-2022	d) Incorporation of bandplans for 122-123, 136-141 and 241-250 GHz to reflect growing usage
2024	
26-Jan-2024	472kHz - remove specific licence terms note - removed in 2023/4 Ofcom licence review
26-Jan-2024	NOTES: 472kHz - 'see licence schedule for additional conditions' remove
26-Jan-2024	28MHz - licensing notes revised
26-Jan-2024	70MHz - added info note regarding 70.5-71.5MHz NoV access
26-Jan-2024	Added new mmWave band pages for 122 and 241GHz, and updates to 134GHz
28-Jan-2024	144MHz - licensing notes revised
28-Jan-2024	430MHz - added extra licensing note re specific conditions within 430-440MHz
28-Jan-2024	24, 47, 76GHz - licensing notes revised
28-Jan-2024	1.3, 2.3, 5.7 and 10GHz licensing notes revised
28-Jan-2024	144.500-144.794 MHz changed from 20kHz to 12 kHz narrowbandwidth operation - for optimised 12.5k channelled usage
28-Jan-2024	145.225 MHz Internet gateways usage added
28-Jan-2024	144.975, 144.9875 MHz paired with 145.575, 145.5875 MHz, now designated for 5W ERP Low power / Adhoc repeaters
28-Jan-2024	433-434MHz revised Note-11 to align with IARU/PU 12.5kHz channelling (was 20kHz BW for 25k spacing)
28-Jan-2024	433-434MHz revised bandwidth column from 20 to 12kHz to realign for 12.5k channelled
28-Jan-2024	433 / 434.6 MHz remove references to 25kHz for 1.6MHz repeater pairs
28-Jan-2024	432.6250-432.6750 MHz Digital communications - remove wording: (25 kHz channels)
28-Jan-2024	433.6250-6750 MHz Digital communications - remove wording: (25 kHz channels)
28-Jan-2024	432.0-432.4 MHz - no formal change yet - but expected to be all 2.7kHz pending IARU confirmation
28-Jan-2024	430MHz - Note-8 - shortened - removed 'attended-only operation in the presence of the NoV holder'
28-Jan-2024	430MHz - further changes may occur subject to Ofcom Coordination notice update
28-Jan-2024	432.0-432.4 MHz narrowband - no formal change yet - but expected to be all 2.7kHz pending IARU confirmation
29-Jan-2024	10GHz - Update Note-4 to remove NoV term
05-Feb-2024	The following are also under review
05-Feb-2024	a) 430-440MHz based on further Ofcom and IARU updates (as per RadCom RSGB Matters)
05-Feb-2024	b) Airborne - nothing specific yet, but do ensure new licence conditions are followed (500mW eirp max Primary bands on)
05-Feb-2024	c) Any other demand/guidance arising from the rollout of revised Ofcom terms
05-Feb-2024	d) HF: IARU review / expansion of data segments
2025 (including some mid-2024+ usage updates)	
20-Dec-2024	434.000 & 438.800MHz Hotspot updates and new Note-4
05-Jan-2025	432.000-432.400MHz narrowband merged to 2.7kHz BW for CW/SSE
08-Jan-2025	432.050 MHz CW centre removed due to usage change
08-Jan-2025	432.370 MHz Meteor Scatter centre of activity removed
02-Feb-2025	2m: Correct omission of 145.2125 MHz FM Internet Gateways
02-Feb-2025	2m: Correct simplex channel designation from V47 to V45
02-Feb-2025	2m: Add 145.2625 MHz FM Internet Gateway
02-Feb-2025	2m: Add 145.3125 MHz FM Internet Gateway
09-Feb-2025	430-440 MHz Note-1 replaced with UK info for Repeater usage/split
09-Feb-2025	430.0125-430.075 MHz Gateway channels expanded to 433.100MHz
09-Feb-2025	430.1250-430.1375 MHz UK DV 9 MHz split repeaters added for (Note-10) usage
09-Feb-2025	430.7875 MHz UR63 UK Reverse 7.6 MHz split repeater - Input added
09-Feb-2025	430.8125-430.9750 MHz RU65-RU78 7.6 MHz split - one extra channel added
09-Feb-2025	431.025-431.250 MHz DV Internet voice gateways expanded from 431.075-431.175
09-Feb-2025	433.000-433.375 MHz Repeater Outputs can now also be from new 5MHz Splits
09-Feb-2025	433.800-434.250 MHz Digital communications & Experiment - Note 3 added
09-Feb-2025	438.000-438.375 MHz RBW00-RBW30 5 MHz split repeater-inputs added
09-Feb-2025	439.9000-439.9875 MHz and Note-9 added for Coordinated low-power apps

Date	Description
2015	
1-Jan-15	Notes Tab - MGM and WSPR notes added
1-Jan-15	Notes Tab - revised text for 472 kHz, 2.3GHz and 3.4GHz due to licence changes
1-Jan-15	146-147MHz: New band plan added copied from October 2014
1-Jan-15	2300-2302MHz: New band plan added, as per RadCom Jan-2014
1-Jan-15	600M: Licensing notes now refer to new licence terms, not NoV
1-Jan-15	600M: Inserted new usage note for 472-475 and 475-479
1-Jan-15	60M: Licensing notes amended to refer to new licence terms, not NoV
1-Jan-15	10M: 29,000-29,100 amended to 6kHz all modes and accomodate AM usage
1-Jan-15	4M: WSPR designation corrected to 70.091, from 70.090 MHz
1-Jan-15	4M: RTTY designation removed from 70.300 MHz
1-Jan-15	2M: Added new 144.000-144.025 All modes / Satellite segment
1-Jan-15	2M: 144.050 MHz Telegraphy calling renamed to Centre
1-Jan-15	2M: 144.300 MHz SSB calling now Centre
1-Jan-15	2M: 144.500 MHz SSTV calling now Image Modes centre
1-Jan-15	2M: 144.525 MHz ATV SSB Talk-back deleted
1-Jan-15	2M: Note-8 simplified for 144.550 AM usage
1-Jan-15	2M: 144.600 RTTY renamed to Data centre of activity (MGM, RTTY, etc.,)
1-Jan-15	2M: 144.700 MHz FAX deleted
1-Jan-15	2M: 144.875-144.9125 packet deleted
1-Jan-15	2M: 144.925-144.950 packet updated
1-Jan-15	2M: 144.975 wideband packet deleted, future usage tbd
1-Jan-15	2M: 145.2125 FM Internet Gateways deleted, Note-13 blanked
1-Jan-15	2M: 145.300 RTTY deleted
1-Jan-15	2M: 145.5875 included for Note-11
1-Jan-15	2M: Note-15 deleted following Packet review
1-Jan-15	13cm: Removed 2350-2390 MHz and Note-4
1-Jan-15	13cm: Realigned usage and Note-1 in 2321-22 to FM/DV as per IARU-R1 plan and to act as a narrowband guardband
1-Jan-15	13cm: Removed EME and altered usage to all modes in 2390-2400
1-Jan-15	13cm: Reduced designationsl in 2310-2320 MHz
1-Jan-15	13cm: Reset 2322-2350 to generic wideband modes
1-Jan-15	9cm: Removed 3410-3475 MHz and Note-4
1-Jan-15	9cm: Added bandwidth column
1-Jan-15	9cm: Revised usage notes, including addition of DATV repeater outputs
1-Jan-15	3cm: Added bandwidth column
1-Jan-15	3cm: Deleted Note-1 as wideband usage is to be aligned based on Note-2
1-Jan-15	3cm: Removed obsolete linear transponder, repeater and datalink usage
1-Jan-15	3cm: Added current TV and Voice Repeater usage
1-Jan-15	3cm: Revised 10-10.125 GHz - including yellow highlight and new Note-4 for Primary User issues
2-Jan-15	Notes Tab - eSSB note added, yellow highlights updated
2-Jan-15	70cm: Note-3 re FAX deleted and removed from 433.700 MHz
2-Jan-15	70cm: 432.700 MHz FAX deleted
2-Jan-15	70cm: 432.600 and 433.600 RTTY deleted
2-Jan-15	70cm: Added missing Licence power restriction for 430-432 MHz
2-Jan-15	70cm: Fixed typo in Note-1 for case of 'i.e.'
2-Jan-15	2300-2302MHz: Power limit corrected
3-Jan-15	70cm: Updated Note-8 for all Internet Gateways as 12.5kHz Channels, 5W (7dBW) max, attended-only
3-Jan-15	70cm: Updated 430.0125-430.0750 MHz Gateways to refer to Note-8
3-Jan-15	70cm: Updated 431.0750-431.1750 MHz Gateways to refer to Note-8
3-Jan-15	70cm: Updated 433.9500-434.0500 MHz Gateways to refer to Note-8
3-Jan-15	70cm: Updated 434.4750-434.5250 MHz Gateways to refer to Note-8
3-Jan-15	70cm: 432.3500 MHz shortened description to Microwave talkback as per 2m, as its not an official calling channel
3-Jan-15	70cm: 432.800 -432.900 UK Beacon band deleted as new frequencies are in the IARU segment
3-Jan-15	70cm: Note-9 re UK beacon band deleted
2016	
30-Nov-15	10M: 29.530 Internet Gateways deleted from IARU Repeater segment
30-Nov-15	10M: 29.630 Internet Gateways deleted from IARU Repeater segment
30-Nov-15	10M: 29.210 Internet Gateways moved to 29.280
30-Nov-15	10M: 29.270 Internet Gateways Channel added
30-Nov-15	160M: Added 32W (15dBW) max Licence Power limit note for 1850-2000 kHz
30-Nov-15	4M: Added 160W (22dBW) Power limit edit
30-Nov-15	6M: Added 100W (20dBW) Power limit to 51-52 MHz Licence note
30-Nov-15	70cm: Neutralised direction for RAYNET 7.6MHz talkthrough on 430.800 / 438.400 MHz
30-Nov-15	Notes: AM bandwidth in all-modes segments clarified
30-Nov-15	70cm: 430.0125-430.0750 MHz Internet voice gateways clarified as FM
30-Nov-15	70cm: 431.0750-431.1750 MHz Internet voice gateways clarified as DV
8-Jan-16	70cm: 432.4000-432.5000 Beacons - Remove obsolete Note-9 reference
28-Jan-16	70cm: 430.400-430.775 MHz UK DV 9 MHz split repeaters - Inputs (Added frequencies)
28-Jan-16	70cm: 439.400-439.775 MHz UK DV 9 MHz split repeaters - Outputs (Added frequencies)
1-Jun-16	30M: Narrowband modes amended to start at 10,130 (was 10,140)
1-Jun-16	80M: 200Hz Narrowband modes segment added at 3,570-3,580 - was Telegraphy only
1-Jun-16	80M: Clarified 3,700-3,775 and 3,775-3,800 (editorial changes only)
1-Jun-16	10M: Clarified 28.320-29,000 (editorial changes only)
1-Jun-16	6M: Deleted 50.401 MHz WSPR beacons +/- 500Hz
1-Jun-16	4M: Deleted 70.091 MHz WSPR beacons +/- 500Hz
1-Jun-16	2M: Deleted 144.4920 MHz +/- 500Hz WSPR beacons
1-Jun-16	146 MHz: Updated NoV expiry wording (editorial)
2017	
17-Jan-17	60M: Note-4 added - Contacts within the UK should avoid the WRC-15 allocation (5351.5 – 5366.5 kHz) if possible
2018	
15-Dec-17	60M: Note-4 has WRC-15 Frequencies added and WRC notes added in Usage column
15-Dec-17	60M: WSPR removed from 5290 kHz
15-Dec-17	60M: 5362-5370 UK Data usage note removed to avoid WRC-15 overlap, WSPR added
15-Dec-17	60M: 5403 USB usage deleted
15-Dec-17	2300 MHz: Updated Licence note as Channel Isles operation is now permitted under latest NoV terms
15-Dec-17	6M: Updated SBP description - deleted 'future'
15-Dec-17	6M: Deleted 50.6 RTTY
15-Dec-17	6M: Added new Note-6 for Digital Experimentation
15-Dec-17	2M: CW Band now starts at 144.100 not 144.110
15-Dec-17	2M: 144.136 PSK31 deleted
15-Dec-17	2M: Unified segments so SSB/MGM etc now runs rom 144.150-144.400
15-Dec-17	2M: Removed unnecessary extra line 144.195-144.205 MHz Random MS SSB as part of simplification
15-Dec-17	2M: Added Personal Weak Signal Beacons (144.491-144.493) in Beacon Guard band
15-Dec-17	2M: Removed 'centre' for Image modes as they are near a band edge
15-Dec-17	2M: Slight changes/clarifications to usage English for RAYNET, MS Calling, Note-7 etc
16-Dec-17	70cm: Beacon band upper limit corrected to IARU 432.490, from 432.500
16-Dec-17	70cm: Added 432.491-432.493 MHz Personal Weak Signal MGM Beacons (BW: 500 Hz max)
16-Dec-17	70cm: 434.4750-434.5250 MHz Internet voice gateways now DV only
16-Dec-17	70cm: 433.8000-434.2500 MHz Digital communications - ADDED ' & Experiments'
16-Dec-17	70cm: Added 434.0000 Low Power Non-NoV Personal Hot-Spot usage
16-Dec-17	70cm: Added 438.8000 Low Power Non-NoV Personal Hot-Spot usage
16-Dec-17	70cm: Editorial - Merged usage for 433.7000-433.7750 MHz (Note 10)
16-Dec-17	70cm: 430.250-430.300 MHz UK DV 9 MHz reverse-split repeaters - Outputs
16-Dec-17	70cm: Added 439.250-439.300 MHz UK DV 9 MHz reverse-split repeaters - Inputs
16-Dec-17	70cm: Deleted 432.0880 MHz PSK31 centre of activity
16-Dec-17	23cm: Added 1296.741-1296.743 MHz Personal Weak Signal MGM Beacons
16-Dec-17	13cm: Updated Note-2 to add 2400-2402 alternative narrowband use in other countries
16-Dec-17	6cm: Introduce BW Column and reformat
16-Dec-17	6cm: Remove 5668 beacons and clarify names for preferred and alternative narrowband centres
16-Dec-17	Notes: Added 5MHz to 'No contests' bands
8-Jan-18	Highlighted Full Licensees Only on 600m, 60m, 146MHz, 2300MHz
8-Jan-18	60M: Clarify it is UK Usage Plan only. Further info - http://rsgb.org/main/operating/band-plans/hf/5mhz/
8-Jan-18	146MHz: Updated Power Limit from 25 to 50W
2019	
3-Dec-2018	2M: Removal of old Microwave talkback from 144.175
3-Dec-2018	2M: More generic Digital Usage term in place of AX25 or TCP/IP usage on 144.925, 144.9375, 144.950
3-Dec-2018	2M: Correction to Simplex Channel designation to V16-V47, (was V16-V48)
3-Dec-2018	2M: Correction to Simplex Channel designation in Footnote-3 to V47 (was V46)

Date	Description
2008	
18-Dec-07	Changes to 75,500 – 76,000MHz allocation, deletion of usage between 142,000 – 144,000MHz
24-Dec-07	Notes moved from "4mm down" worksheet to the new "Notes" worksheet. Notes from the IARU Region 1 Band Plan added to this new worksheet.
2009	
23-Nov-08	Changed the effectivity date for 40m band plan to 29/3/09 and amended all other to 1/1/09
23-Nov-08	Changed the note re date of conference from which the band plan is taken - note that this change is made on each worksheet
23-Nov-08	Complete change to 40m band plan, inc notes on the same worksheet
23-Nov-08	Added in QRP CoA at 18.130kHz and 18.150kHz digital voice centre of activity to 17m plan
23-Nov-08	Added in QRP CoA at 24.950kHz and 24.960kHz digital voice centre of activity to 12m plan
23-Nov-08	Added 3.630kHz - digital voice Centre of Activity to 80m plan
23-Nov-08	Added 14.130kHz - digital voice centre of activity to 20m plan
23-Nov-08	Added 21.180kHz - digital voice centre of activity to 15m plan
23-Nov-08	Added 28.330kHz - digital voice centre of activity to 10m plan
23-Nov-08	Complete change to 136kHz plan
25-Nov-08	6M Band Plan: added 50.400MHz WSPR beacons
25-Nov-08	6M Band Plan: 50.710-50.910MHz: added DV to FM repeater outputs
25-Nov-08	6M Band Plan: 51.210-51.410MHz: added DV to FM repeater inputs + (Note 4)
25-Nov-08	6M Band Plan: 51.430-51.690MHz: added DV to FM simplex channels + (Note 4) also added simplex for clarification
25-Nov-08	6M Band Plan: added 'IARU common channels' designation to Internet gateways
25-Nov-08	6M Band Plan: added Note 4
26-Nov-08	4M Band Plan: 70.030MHz: added WSPR beacons
26-Nov-08	2M Band Plan: DELETED 144.000-144.035 MHz Moonbounce (EME) exclusive
26-Nov-08	2M Band Plan: DELETED 144.120-144.150 MHz Moonbounce(EME) MGM (JT65)
26-Nov-08	2M Band Plan: DELETED 144.150-144.160 MHz FAI and Moonbounce (EME) activity SSB
26-Nov-08	2M Band Plan: added EME MGM activity (Note 7)
26-Nov-08	2M Band Plan: 144.000-144.110MHz: added Telegraphy (including EME CW) to Usage column
26-Nov-08	2M Band Plan: 144.110-144.150MHz: added Telegraphy and MGM to Usage column
26-Nov-08	2M Band Plan: 144.150-144.180MHz: added Telegraphy, MGM and SSB to Usage column
26-Nov-08	2M Band Plan: 144.490-144.500MHz: added 144.4905MHz +/- 500Hz WSPR beacons and beacon guard band
26-Nov-08	2M Band Plan: 144.900-145.1935MHz: added DV to FM repeater inputs + (Note 5)
26-Nov-08	2M Band Plan: 145.5935-145.7935MHz: added DV to FM repeater outputs
26-Nov-08	2M Band Plan: 145.720-145.935MHz: added DV to FM simplex channels + (Note 5)(Note-6)
26-Nov-08	2M Band Plan: added 144.6125 MHz UK Digital Voice (DV) calling + (Note 5) (Note 6)(Note-6)
26-Nov-08	2M Band Plan: added 'IARU Common Channels' designation to 145MHz Internet Gateways
26-Nov-08	2M Band Plan: added Note 5
26-Nov-08	2M Band Plan: added Note 6
26-Nov-08	2M Band Plan: added Note 7
26-Nov-08	2M Band Plan: added Note 8
27-Nov-08	70cm Band Plan: 432.9940-433.3810: added DV to FM repeater outputs
27-Nov-08	70cm Band Plan: 434.5940-434.9810: added DV to FM repeater outputs + (Note 12)
27-Nov-08	70cm Band Plan: 433.3940-433.5810MHz added DV to FM simplex channels + (Note 12), (Note 13)
27-Nov-08	70cm Band Plan: 433.450MHz: added Note 5 and 438.6125 for Digital Voice (DV) calling
27-Nov-08	70cm Band Plan: added Note 12
27-Nov-08	70cm Band Plan: added Note 13
29-Nov-08	23cm Band Plan: added Notes 5, 6
29-Nov-08	23cm Band Plan: added Notes 7, 8
29-Nov-08	23cm Band Plan: amended 1298.500-1296.800 - Image/ Data Centres & Transponder Outputs
29-Nov-08	23cm Band Plan: added DV to FM Repeater and Simplex segments (Notes-5, 6) plus reformatting
29-Nov-08	23cm Band Plan: added 'IARU common channels' designation to 1297 FM Gateways
29-Nov-08	23cm Band Plan: added 1296.750-1296.800 Local Beacons, 10W erp max
29-Nov-08	13cm Band Plan: added 2320.750-2320.800 Local Beacons, 10W erp max
30-Nov-08	9cm band Plan: added migration of EME activity from 3456 to 3400MHz + (Note 1)
30-Nov-08	9cm Band Plan: added 3400.750-3400.800 and designations for Local & Propagation Beacons
30-Nov-08	9cm Band Plan: DELETED 3456 MHz designation
30-Nov-08	9cm Band Plan: added 3400.750-3400.800 and designations for Local & Propagation Beacons
30-Nov-08	9cm Band Plan: added new 3402-3410 & 3410-3475MHz segments (Notes-2,3)
30-Nov-08	9cm Band Plan: added Note 2 and Note 3
30-Nov-08	6cm Band Plan: added 5760 MHz designations for Local & Propagation Beacons and 5668.8 usage
30-Nov-08	3cm Band Plan: added 10368.750-10369.800 and designations for Local & Propagation Beacons
30-Nov-08	12mm Band Plan: added 24048.750-24048.800 and designations for Local & Propagation Beacons
30-Nov-08	Formatting corrections on most microwave bands for Service/User descriptions
30-Nov-08	Added Digital Voice DV note to main Notes page
1-Dec-08	40m Band Plan: Clarified Amateur Satellite Service Licence Note for 7.1-7.2 MHz
1-Dec-08	Added 50.630MHz for Digital Voice
15-Dec-08	Change to the frequencies in the 7MHz note
17-Dec-08	70cm Band Plan: removed reference to 20 kHz necessary bandwidth at 435.000-438.000MHz
23-Dec-08	Added note "Where no DX traffic is involved, the contest segment should not include 7.175 - 7.200kHz"
9-Jan-09	Editorial changes to sub-header and some cell formatting changes.
14-Jan-09	Typo corrections on 2.3GHz Note-2 and 3.4 GHz Note-1
6-Mar-09	Corrected QRP freq on 17m band to 18086kHz
2010	
12-Dec-09	Added 51.510MHz FM calling frequency
21-Dec-09	Amended Notes 3&8 in the 23cm Band Plan (esp for 1240/1MHz & 1298/9MHz areas) to emphasise replanning
21-Dec-09	Added new Note 4 to 3410-3475MHz range
21-Dec-09	Corrected Narrowband BW to 500Hz on Notes page
21-Dec-09	Added Beacons and 1.3GHz to Notes Page
2-Jan-10	Added words "Propagation Beacons only" to 432.4000-432.5000 MHz record
2-Jan-10	Highlighted 432.8000-432.9000 MHz line in RED and made the words read "UK Beacons (Note 9)"
8-Jan-10	Changed the word "Bandplan" to "Band Plan"
26-Jan-10	In "Notes" worksheet "Experimentation with NBFM Packet Radio on 29 MHz": 20.210 changed to 29.210 & "included" changed to "inclusive"
2012	
16-Dec-11	40M: Added Note 2 on Data and PSK31 at 7040kHz since the 2008 re-plan
16-Dec-11	40M: Deleted CW contest preferred segment; reformatted 7,060-7,100 MHz
16-Dec-11	10M: Amended FM/Repeater channels as per Sun City 2011
16-Dec-11	6M: 50.000-50.500 MHz major changes as per Sun City 2011
16-Dec-11	6M: 50.700-52.000 MHz changes for RAYNET, 23kHz and added IARU Repeater Outputs
16-Dec-11	4M: Changes to narrowband and beacon frequencies
16-Dec-11	2M: Footnote 10 added for RAYNET Changes
16-Dec-11	2M: Footnote 11 added for 144.975/145.575
16-Dec-11	70cm: Footnote 10 amended for RAYNET Changes
16-Dec-11	70cm: 437MHz designated for DATV centre of activity
16-Dec-11	70cm: Deleted MPT1327 designations. Added DV 9MHz split repeaters (approx freqs)
16-Dec-11	23cm: Widespread changes to data and repeater allocations -inc new Note 9
16-Dec-11	23cm: deleted 1296.370 FSK441 as per Sun City 2011
16-Dec-11	23cm: replaced 1298-1300 MHz with Sun City 2011 recommendations
16-Dec-11	13cm: Amended narrowband BW, replaced packet, updated formatting
16-Dec-11	76GHz: Other bands info moved to bottom of new 134GHz tab
16-Dec-11	134GHz: Added new bandplan tab inc new 134.928 MHz narrowband segment
5-Apr-12	Corrected Telegraphy typos for 80 and 20m band
5-Apr-12	Clarify VHF calling freqs, DV vs FM operating (added Note-12)
5-Apr-12	Removed redundant AM footnote from 30m
16-Jul-12	4M: Corrected WSPR beacons frequency typo (from 70.091 to 70.090 MHz)
16-Jul-12	2M: Updated band plan for Digital Communications in 144.8-145.0 MHz (esp for DV & FM Internet Gateways)
16-Jul-12	2M: 145.2125 specifically for FM Gateways (though assignments may be reduced to protect 145.200 MHz E-S uplinks)
2013	
9-Dec-12	Added Intro Tab
9-Dec-12	Amendments Tab split into Latest and Older Changes Tabs
9-Dec-12	Amended Notes Tab for clarifications for AM Operation, 472kHz, 5MHz, 2.3GHz, 3.4GHz
9-Dec-12	136kHz: Updated countries in Radio Reg note - removed Libya, added South Sudan
9-Dec-12	2M: amended 144.600 RTTY to Centre of Activity, DELETED superfluous second 144.600 RTTY line
9-Dec-12	13cm: Added Note-4 and highlight due to spectrum release expected in 2350-2390 MHz
9-Dec-12	9cm: Highlighted 3410+ spectrum release area (Note-4)
9-Dec-12	10GHz: replaced 10,080 MHz packet links
12-Dec-12	600M: Added tab for new WRC-12 band - 472-479 kHz
12-Dec-12	60M: Added tab for UK 5MHz (experimental) frequencies
19-Dec-12	80M: Added missing 2.7kHz Bandwidth text at 3,775-3,800kHz.
19-Dec-12	600M: Amended Note-3 to clarify AM usage/bandwidth
19-Dec-12	2M: Added Note-13 for withdrawal of 145.2125 FM Gateways
19-Dec-12	70cm: Note-14 added for 437MHz DATV
19-Dec-12	23cm: Note-10 added for 23cm DATV
19-Dec-12	Finalised Notes Tab and new 60m tab
16-Jan-13	Updated Intro Tab, page margins
22-Jul-13	10M: Removed downlink-only restriction on 29.3-29.5 MHz Amateur Satellites
22-Jul-13	60M: Highlighted line added for 5290 kHz Beacons and WSPR
22-Jul-13	4M: Fax designation removed from 70.300 MHz
22-Jul-13	2M: WSPR Changed from 144.4905 to 144.4920 MHz
22-Jul-13	2M: Note-16 added to highlight NBFM, to facilitate move of DV Gateway use from 144.875 to 144.8125
22-Jul-13	2M: 'IARU Common Channel' designation added to most 144.8 DV Gateway frequencies
22-Jul-13	70cm: Deletion of 439.9875 POCSAG Centre
22-Jul-13	70cm: Deletion of 432.5-432.6 Linear Transponder Inputs
22-Jul-13	70cm: Deletion of 432.5-432.6 Linear Transponder Outputs
29-Jul-13	136kHz - Power limit text amended to 'erp' as per UK license, from 'eipr'
29-Jul-13	60M: Added UK Frequency Usage notes for CW QRP, Emergency Comms and Data modes
29-Jul-13	60M: Moved all-modes/bandwidth note to below table
29-Jul-13	6M: Added Note-6 re migration of Gateways from 51.9 MHz, to 50.5 MHz IARU Common Channels
2014	
27-Nov-13	6M: 51.9 MHz Gateways and Note-6 deleted, following migration to 50.5 MHz IARU Common channels
27-Nov-13	6M: Merged IARU-aligned Repeater Outputs at 51.9MHz to a single block following Gateway migrations to 50.5MHz
27-Nov-13	2M: 144.8125 MHz now IARU Common channel for DV gateways (moved from 144.875)
27-Nov-13	2M: 144.875 MHz vacant channel now 'td' following completion of IARU DV Gateway alignments
27-Nov-13	2M: Updated Note-14 to emphasise NBFM use of 144.800
27-Nov-13	2M: Added Note-15 to indicate 144.875 - 144.975 designations are subject to review and potential change
15-Dec-13	60M: Added 5,317 kHz - AM 6kHz max. bandwidth
15-Dec-13	60M: Added 5,403.5kHz - USB common international frequency

Notes to the Band Plan

ITU-R radio regulation RR 1.152 and Recommendation SM.328 (extract):

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

All Modes	CW, SSB and those modes listed as Centres of Activity, plus AM (Consideration should be given to adjacent channel users.
Image Modes	Any analogue or digital image modes within the appropriate bandwidth, for example SSTV and Fax
Narrow band modes	All modes using up to 500Hz bandwidth, including CW, RTTY, PSK, etc
Digimodes	Any digital mode used within the appropriate bandwidth, for example RTTY, PSK, MT63, etc
Sideband usage	Below 10MHz use lower sideband (LSB), above 10MHz use upper sideband (USB). Note the lowest dial settings for LSB Voice modes are 1843, 3603 and 7053kHz on 160, 80 and 40m. Note that on 5MHz USB is used.
Amplitude Modulation (AM)	Amplitude Modulation (AM) with a bandwidth greater than 2.7kHz is acceptable in the all-modes segments provided users consider adjacent channel activity when selecting operating frequencies (Davos 2005)
Extended SSB (eSSB)	Extended SSB (eSSB) is only acceptable in the all-modes segments provided users consider adjacent channel activity when selecting operating frequencies
Digital Voice (DV)	Users of Digital Voice (DV) should check that the channel is not in use by other modes (CT08_C5_Rec20).
FM Repeater & Gateway Access	CTCSS Access is recommended. Toneburst access is being withdrawn in line with IARU-R1 recommendations
Beacons	Propagation Beacon Sub-bands are highlighted - Please avoid transmitting in them!!
MGM	M(achine) G(enerated) M(ode) indicates those transmission modes relying fully on computer processing such as RTTY, AMTOR, PSK31, JTxx, FSK441 and the like. This does not include Digital Voice (DV) or Digital Data (DD)
WSPR	Above 30 MHz, WSPR frequencies in the band plan are the centre of the transmitted frequency (not the suppressed carrier frequency or the VFO dial setting).
Transmitter Setup and Linearity	Close attention should be given to power amplifier linearity to control the final transmitted bandwidth and avoid spectral regrowth affecting adjacent users. In particular this can be a major issue when operating digital modes. It is recommended that operators do not use more power than is necessary, and that care is taken to ensure sound cards, interfaces, and other equipment are properly set up so as to minimise the potential for interference.

CW QSOs are accepted across all bands, except within beacon segments (Recommendation DV05_C4_Rec_13)

Contest activity shall not take place on the 5, 10, 18 and 24MHz bands

Non-contesting radio amateurs are recommended to use the contest-free HF bands (30, 17 and 12m) during the largest international contests (DV05_C4_Rev_07)

The term "automatically controlled data stations" include Store and Forward stations.

Transmitting frequencies

The announced frequencies in the band plan are understood as "transmitted frequencies" (not those of the suppressed carrier!)

Centre of Activity (CoA)	A guide to where users of a particular mode or activity tend to operate. The bandplan does not give such users precedence over other modes or activities
---------------------------------	--

Unmanned transmitting stations

IARU member societies are requested to limit this activity on the HF bands. It is recommended that any unmanned transmitting stations on HF shall only be activated under operator control except for beacons agreed with the IARU Region 1 Beacon Coordinator, or specially licensed experimental stations.

472-479 kHz

Access is available to Full Licensees only

1.8MHz

Radio Amateurs in countries that have a SSB allocation ONLY below 1840kHz, may continue to use it, but the National Societies in those countries are requested to take all necessary steps with their licence administrations to adjust phone allocations in accordance with the Region 1 Band Plan (UBA - Davos 2005)

3.5MHz

Inter-Continental operations should be given priority in the segments 3500 - 3510kHz and 3775 - 3800kHz

Where no DX traffic is involved, the contest segments should not include 3500 - 3510kHz or 3775 - 3800kHz. Member societies will be permitted to set other (lower) limits for national contests (within these limits).

3510 - 3600kHz may be used for unmanned ARDF beacons (CW, A1A) (Recommendation DV05_C4_Rec_12)

5MHz

Access is available to Full Licensees only - see licence schedule for additional conditions

7MHz

The band segment 7040 - 7060kHz may be used for automatic controlled data stations (unattended) traffic in the areas of Africa south from the equator during local daylight hours.

Where no DX traffic is involved, the contest segment should not include 7,175 - 7,200kHz.

10MHz

SSB may be used during emergencies involving the immediate safety of life and property and only by stations actually involved in the handling of emergency traffic

The band segment 10120kHz to 10140kHz may be used for SSB transmissions in the area of Africa south of the equator during local daylight hours.

News bulletins on any mode should not be transmitted on the 10MHz band.

28MHz

Operators should not transmit on frequencies between 29.3 and 29.51MHz to avoid interference to amateur satellite downlinks

Experimentation with NBFM Packet Radio at 29MHz:

Preferred operating frequencies on each 10kHz from 29.210 to 29.290MHz inclusive should be used. A deviation of +/- 2.5kHz being used with 2.5kHz as maximum modulation frequency.

1.3GHz

The band is subject to re-planning. It is also shared with air traffic radar

2.3 GHz (2310-2350 and 2390-2400MHz)

Operation is subject to specific licence conditions and guidance - see also the Ofcom PSSR statement

3.4GHz (3400-3410 MHz)

Operation is subject to specific licence conditions and guidance - see also the Ofcom PSSR statement

Innovation Bands: 70.5-71.5 MHz, 146-147 MHz, 2300-2302 MHz and >275 GHz

Access to these bands requires an appropriate NoV, which is available to Full Licensees only

RSGB Band Plan (effective from 1st January 2022)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on on frequencies above 430 MHz.

136 kHz	Necessary Bandwidth	UK Usage
135.7-137.8 kHz	200	CW, QRSS and narrow-band digital modes
LICENCE NOTES: Amateur Service - Secondary User . 1 Watt (0 dBW) erp		

R.R. 5.67B The use of the band 135.7-137.8kHz in Algeria, Egypt, Iraq, Lebanon, Syrian Arab Repub Sudan, South Sudan and Tunisia is limited to fixed and maritime mobile services. The amateur service shall not be used in the above-mentioned countries in the band 135.7-137.8kHz, and this should be taken into account by the countries authorising such use (WRC-19)

RSGB Band Plan (effective from 1st January 2024)

IARU Region-1 does not have a formal band plan for this allocation, but has a usage recommendation (Note-1)

Access to this band is available to Full Licensees only

472 kHz (600m)	Necessary Bandwidth	UK Usage
472-479 kHz (Note-2)	500	CW, QRSS and narrow-band digital modes (Note-1)
Note-1: Usage recommendation: - 472-475 kHz CW-only 200Hz max BW, 475-479 kHz - CW & Digimodes Note-2: It should be emphasised that this band is available on a non-interference basis to existing services. UK amateurs should be aware that some overseas stations may be restricted in their use of transmit frequency in order avoid interference to nearby radionavigation service Non-Directional Beacons LICENCE NOTES: Amateur Service Secondary User. Full Licensees only - 5 Watts eirp maximum		

R.R. 5.80B The use of the frequency band 472-479 kHz in Algeria, Saudi Arabia, Azerbaijan, Bahrain, Belarus, China, Comor Djibouti, Egypt, United Arab Emirates, the Russian Federation, Iraq, Jordan, Kazakhstan, Kuwait, Lebanon, Libya, Mauritania, Oman, Uzbekistan, Qatar, Syrian Arab Republic, Kyrgyzstan, Somalia, Sudan, Tunisia and Yemen is limited to the maritime mobile and aeronautical radionavigation services. The amateur service shall not be used in the above-mentioned countries in this frequency band, and this should be taken into account by the countries authorizing such use. (WRC 12)

RSGB Band Plan (effective from 1st January 2016)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

1.8 MHz (160m)	Necessary Bandwidth	UK Usage
1,810-1,838 kHz	200 Hz	Telegraphy
1,838-1,840	500 Hz	Narrow band modes
1,840-1,843	2.7 kHz	All modes
1,843-2,000	2.7 kHz	Telephony (Note 1), Telegraphy 1,836 kHz QRP (low power) Centre of Activity, 1,960 kHz DF Contest beacons (14dBW)
Note 1: Lowest LSB carrier frequency (dial setting) should be 1,843 kHz. AX25 packet should not be used on the 1.8 MHz band. LICENCE NOTES: 1,810-1,850 kHz Primary User: 1810-1830 kHz on a non-interference basis to stations outside of the UK. 1,850-2,000 kHz Secondary User: 32W (15dBW) Maximum		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st June 2016)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on on frequencies above 430 MHz.

3.5 MHz (80m)	Necessary Bandwidth	UK Usage
3,500-3,510 kHz	200 Hz	Telegraphy - Priority for inter-continental operation
3,510-3,560	200 Hz	Telegraphy - contest preferred. 3,555 kHz - QRS (slow telegraphy) Centre of Activity
3,560-3,570	200 Hz	Telegraphy 3,560 kHz - QRP (low power) Centre of Activity
3,570-3,580	200 Hz	Narrow band modes
3,580-3,590	500 Hz	Narrow band modes
3,590-3,600	500 Hz	Narrow band modes - automatically controlled data stations (unattended)
3,600-3,620	2.7 kHz	All modes - automatically controlled data stations (unattended), (Note 1)
3,600-3,650	2.7 kHz	All modes - Phone contest preferred, (Note 1). 3,630kHz - digital voice Center of Activity
3,650-3,700	2.7 kHz	All modes - Telephony, Telegraphy 3,663 kHz may be used for UK emergency comms traffic. 3,690 kHz SSB QRP (low power) Centre of Activity.
3,700-3,775	2.7 kHz	All modes - Phone contest preferred 3,735 kHz Image mode Centre of Activity 3,760 kHz IARU Region 1 Emergency Centre of Activity
3,775-3,800	2.7 kHz	All modes - Phone contest preferred Priority for inter-continental telephony (SSB) operation
Note 1: Lowest LSB carrier frequency (dial setting) should be 3,603 kHz.		
LICENCE NOTES: Primary User: Shared with other user services:		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Usage Plan (effective from 1st January 2018)

Access to this band is available to Full Licensees only

See Licence Schedule notes for specific conditions

5 MHz (60m)	Available Width	UK Usage
5258.5 - 5264.0 kHz	5.5 kHz	5262 kHz - CW QRP Centre of Activity
5276.0 - 5284.0	8 kHz	5278.5 kHz - may be used for UK emergency comms traffic
5288.5 - 5292.0	3.5 kHz	Beacons on 5290 kHz (Note-2)
5298.0 - 5307.0	9 kHz	
5313.0 - 5323.0	10 kHz	5317 kHz - AM 6kHz max. bandwidth
5333.0 - 5338.0	5 kHz	
5354.0 - 5358.0	4 kHz	Within WRC-15 Band
5362.0 - 5374.5	12.5 kHz	Partly within WRC-15 band, WSPR
5378.0 - 5382.0	4 kHz	
5395.0 - 5401.5	6.5 kHz	
5403.5 - 5406.5	3 kHz	
Unless indicated, usage is all-modes (necessary bandwidth to be within channel limits) Note 1: Upper Sideband is recommended for SSB activity. Note 2: Activity should avoid interference to the experimental beacons on 5290 kHz Note 3: Amplitude Modulation is permitted with a maximum bandwidth of 6kHz, on frequencies with at least 6kHz available width Note 4: Contacts within the UK should avoid the WRC-15 band (5351.5 - 5366.5 kHz) if possible For the latest current guidance refer to the RSGB website LICENCE NOTES: Full Licensees only Secondary User: 100W max Note that specific conditions regarding operating, transmission bandwidth, power and antennas are specified in the Licence		

Notes to the Usage Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

RSGB Band Plan (effective from 1st January 2012)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

7 MHz (40m)	Necessary Bandwidth	UK Usage
7,000-7,040 kHz	200 Hz	Telegraphy. 7,030 kHz - QRP Centre of Activity
7,040-7,047	500 Hz	Narrow band modes (Note 2)
7,047-7,050	500 Hz	Narrow band modes , automatically controlled data stations (unattended)
7,050-7,053	2.7 kHz	All modes , automatically controlled data stations (unattended), (Note 1)
7,053-7,060	2.7 kHz	All modes , digimodes
7,060-7,100	2.7 kHz	All modes , SSB Contest Preferred Segment digital voice 7,070kHz; SSB QRP Centre of Activity 7,090 kHz;
7,100-7,130	2.7 kHz	All modes , 7,110kHz - Region 1 Emergency Centre of Activity.
7,130-7,200	2.7 kHz	All modes , SSB Contest Preferred Segment; 7,165kHz - Image Centre of Activity
7,175-7,200	2.7 kHz	All modes , priority for intercontinental operation
Note 1: Lowest LSB carrier frequency (dial setting) should be 7,053 kHz. Note 2: PSK31 activity starts from 7,040kHz. Since 2009, the narrow band modes segment starts at 7,040kHz. LICENCE NOTES: 7,000-7,100 kHz Amateur and Amateur Satellite Service - Primary User . 7,100-7,200 kHz Amateur Service - Primary User .		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st June 2016)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

10 MHz (30m)	Necessary Bandwidth	UK Usage
10,100-10,130 kHz	200 Hz	Telegraphy (CW) 10,116 kHz - QRP (low power) Centre of Activity Narrow band modes Automatically controlled data stations (unattended) should avoid the use of the 10 MHz band
10,130-10,150	500 Hz	
The 10 MHz band is allocated to the Amateur Service only on a Secondary basis. The IARU has agreed that only CW and other narrow bandwidth modes are to be used on this band. Likewise the band is not to be used for contests and bulletins. SSB may be used on the 10 MHz band during emergencies involving the immediate safety of life and property, and only by stations actually involved with the handling of emergency traffic. The band segment 10,120-10,140 kHz may only be used for SSB transmissions in the area of Africa south of the equator during local daylight hours. LICENCE NOTES: Amateur Service - Secondary User.		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2009)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on on frequencies above 430 MHz.

14MHz (20m)	Necessary Bandwidth	UK Usage
14,000-14,060 kHz	200 Hz	Telegraphy - contest preferred 14,055 kHz QRS (slow telegraphy Centre of Activity)
14,060-14,070	200 Hz	Telegraphy 14,060 kHz QRP (low power) Centre of Activity
14,070-14,089	500 Hz	Narrow band modes
14,089-14,099	500 Hz	Narrow band modes - automatically controlled data stations (unattended)
14,099-14,101		IBP - reserved exclusively for beacons
14,101-14,112	2.7 kHz	All modes - automatically controlled data stations (unattended)
14,112-14,125	2.7 kHz	All modes (excluding digimodes)
14,125-14,300	2.7 kHz	All modes - SSB contest preferred segment 14,130kHz - digital voice centre of activity 14,195+- 5 kHz Priority for Dxpeditions 14,230 kHz - Image Centre of Activity. 14,285 kHz - QRP Centre of Activity
14,300-14,350	2.7 kHz	All modes 14,300 kHz Global Emergency Centre of Activity
LICENCE NOTES: Amateur Service - Primary User. 14,000-14,250 kHz Amateur Satellite Service - Primary User.		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2009)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

18 MHz (17m)	Necessary Bandwidth	UK Usage
18,068-18,095 kHz	200 Hz	Telegraphy 18,086 kHz QRP (low power) Centre of Activity.
18,095-18,105	500 Hz	Narrow band modes
18,105-18,109	500 Hz	Narrow band modes - automatically controlled data stations (unattended)
18,109-18,111		IBP - reserved exclusively for beacons
18,111-18,120	2.7 kHz	All modes - automatically controlled data stations (unattended)
18,120-18,168	2.7 kHz	All modes , 18,130kHz SSB QRP centre of activity 18,150kHz digital voice centre of activity 18,160 kHz Global Emergency Centre of Activity
LICENCE NOTES: Amateur and Amateur Satellite Service- Primary User . The band is not to be used for contests or bulletins.		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2021)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

21 MHz (15m)	Necessary Bandwidth	UK Usage
21,000-21,070 kHz	200 Hz	Telegraphy 21,055 kHz QRS (slow telegraphy) Centre of Activity. 21,060 kHz QRP (low power) Centre of Activity
21,070-21,090	500 Hz	Narrow band modes
21,090-21,110	500 Hz	Narrow band modes - automatically controlled data stations (unattended)
21,110-21,120	2.7 kHz	All modes (excluding SSB) - automatically controlled data stations (unattended)
21,120-21,149	500 Hz	Narrow band modes
21,149-21,151		IBP - reserved exclusively for beacons
21,151-21,450	2.7 kHz	All modes. 21,180kHz - digital voice centre of activity 21,285 kHz - QRP Centre of Activity. 21,340 kHz - Image Centre of Activity. 21,360 kHz - Global Emergency Centre of Activity
Note 1: 21,125-21,245 is also designated for use by amateur satellites		
LICENCE NOTES: Amateur and Amateur Satellite Service- Primary User .		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2009)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

24 MHz (12m)	Necessary Bandwidth	UK Usage
24,890-24,915 kHz	200 Hz	Telegraphy 24,906 kHz QRP (low power) centre of activity
24,915-24,925	500 Hz	Narrow band modes
24,925-24,929	500 Hz	Narrow band modes - automatically controlled data stations (unattended)
24,929-24,931		IBP - reserved exclusively for beacons
24,931-24,940	2700	All modes - automatically controlled data stations (unattended)
24,940-24,990	2700	All modes , 24,950kHz SSB QRP Centre of Activity 24,960kHz digital voice centre of activity
LICENCE NOTES: Amateur and Amateur Satellite Service- Primary User . The band is not to be used for contests or bulletins.		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2024)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on on frequencies above 430 MHz.

28 MHz (10m)	Necessary Bandwidth	UK Usage
28,000-28,070 kHz	200 Hz	Telegraphy 28,055 kHz QRS (slow telegraphy) Centre of Activity. 28,060 kHz QRP (low power) Centre of Activity.
28,070-28,120	500 Hz	Narrow band modes
28,120-28,150	500 Hz	Narrow band modes - automatically controlled data stations (unattended)
28,150-28,190	500 Hz	Narrow band modes
28,190-28,199		IBP - regional time shared beacons
28,199-28,201		IBP - world wide time shared beacons
28,201-28,225		IBP - continuous-duty beacons
28,225-28,300	2.7 kHz	All modes - beacons
28,300-28,320	2.7 kHz	All modes - automatically controlled data stations (unattended)
28,320-29,000	2.7 kHz	All modes 28,330 kHz - Digital Voice centre of activity 28,360 kHz - QRP Centre of Activity. 28,680 kHz - Image Centre of Activity.
29,000-29,100	-	All modes - See Note-1 regarding 29,000-29,510 kHz
29,100-29,200	-	All modes - FM simplex - 10 kHz channels
29,200-29,300	-	All modes - automatically controlled data stations (unattended) 29,270 kHz UK Internet voice gateway - unattended 29,280 kHz UK Internet voice gateway - unattended 29,290 kHz UK Internet voice gateway - unattended
29,300-29,510	-	Satellite links
29,510-29,520		Guard channel
29,520-29,590	6 kHz	All modes - FM repeater inputs (RH1-RH8)
29,600	6 kHz	All modes - FM calling channel
29,610	6 kHz	All modes - FM simplex repeater (parrot) - input and output
29,620-29,700	6 kHz	All modes - FM repeater outputs (RH1-RH8)
Note-1: Experimental wide bandwidth operation within 29,000 - 29510 must be on a non-interference basis to other stations, including the amateur satellite service segment at 29300 - 29510 kHz.		
LICENCE NOTES: Amateur and Amateur Satellite Service- Primary User . Note specific conditions apply within 50km of NGR SK985640 (Waddington)		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2021)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

50 MHz (6m)	Necessary Bandwidth	UK Usage
50.000-50.100 MHz	500 Hz	Telegraphy Only (except for Beacon Project) Note-2 50.000-50.030 MHz reserved for Synchronised Beacon Project (Note 2) Region-1: 50.000-50.010; Region-2: 50.010-50.020; Region-3: 50.020-50.030
50.100-50.200	2.7 kHz	50.050 MHz Future International Centre of Activity 50.090 MHz Intercontinental DX Centre of Activity (Note 1) SSB/Telegraphy - International Preferred 50.100-50.130 MHz Intercontinental DX Telegraphy & SSB (Note 1) 50.110 MHz Intercontinental DX Centre of Activity 50.130-50.200 MHz General International Telegraphy & SSB 50.150 MHz International Centre of Activity
50.200-50.300	2.7 kHz	SSB/Telegraphy - General Usage 50.285 MHz Crossband Centre of Activity
50.300-50.400	2.7 kHz	MGM/Narrowband/Telegraphy 50.305 MHz PSK Centre of Activity 50.310-50.320 MHz EME 50.320-50.380 MHz MS
50.400-50.500		Propagation Beacons Only
50.500-50.700	-	All Modes. 50.520 MHz FM/DV Internet voice gateway 50.530 MHz FM/DV Internet voice gateway 50.540 MHz FM/DV Internet voice gateway 50.600-50.700 MHz Digital communications 50.630 MHz Digital Voice (DV) calling
50.700-50.900	12 kHz	50.710-50.890 MHz FM/DV Repeater Outputs (10 kHz channel spacing)
50.900-51.200	-	All Modes
51.200-51.400	12 kHz	51.210-51.390 MHz FM/DV Repeater Inputs (10 KHz channel spacing) (Note 4)
51.400-52.000	-	All Modes 51.410-51.590 MHz FM/DV Simplex (Note 3) (Note 4) 51.510 MHz FM calling frequency 51.530 MHz GB2RS news broadcast and slow morse 51.650 & 51.750 MHz See Note 5 (25kHz aligned) 51.970 & 51.990 MHz See Note 5
Note 1: Only to be used between stations in different continents (not for intra-European QSOs). Note 2: 50.0-50.1MHz is currently shared with Propagation Beacons. These are due to be migrated to 50.4-50.5 MHz, to create more space for Telegraphy and a new Synchronised Beacon Project Note 3: 20 kHz channel spacing. Channel centre frequencies start at 51.430 MHz. Note 4: Embedded data traffic is allowed with digital voice (DV) Note 5: May be used for Emergency Communications and Community Events Note-6: Digital Experiments to support innovation may occur around 50.6, 51.0 or 51.7 MHz with maximum bandwidths of 50, 200 and 500 kHz respectively on a shared non-interference basis LICENCE NOTES : Amateur Service 50.0-51.0 MHz - Primary User. Amateur Service 51.0-52.0 MHz - Secondary User: 100W (20dBW) max Available on the basis on non-interference to other services (inside or outside the UK).		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2021)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

70 MHz (4m)	Necessary Bandwidth	UK Usage (Note 1)
70.000-70.090 MHz	1 kHz	Propagation Beacons only
70.090-70.100	1 kHz	Personal Beacons
70.100-70.250	2.7 kHz	Narrow Band modes 70.185 MHz Cross-band activity centre 70.200 MHz CW/SSB centre 70.250 MHz MS centre
70.250-70.294	12 kHz	All Modes 70.260 MHz AM/FM calling 70.270 MHz MGM centre of activity
70.294-70.500	12 kHz	All modes channelised operations using 12.5 kHz spacing. 70.3000 MHz 70.3125 MHz Digital modes 70.3250 MHz DX Cluster 70.3375 MHz Digital modes 70.3500 MHz Internet voice gateway (Note 2) 70.3625 MHz Internet voice gateway 70.3750 MHz See Note 2 70.3875 MHz Internet voice gateway 70.4000 MHz See Note 2 70.4125 MHz Internet voice gateway 70.4250 MHz FM simplex - used by GB2RS news broadcast 70.4375 MHz Digital modes (special projects) 70.4500 MHz FM calling 70.4625 MHz Digital modes 70.4750 MHz 70.4875 MHz Digital modes
Note 1: Usage by operators in other countries may be influenced by restrictions in their national allocations Note 2: May be used for Emergency Communications and Community Events LICENCE NOTES: Amateur Service 70.0-70.5 MHz Secondary User: 160W (22dBW) Maximum Available on the basis of non-interference to other services (inside or outside the UK).		

Notes to the Band Plan

Note-1: Access to 70.5 - 71.5 MHz by Full Licensees is also possible by NoV

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2025)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

144 MHz (2m)	Necessary Bandwidth	UK Usage
144.000-144.025 MHz 144.025-144.100 MHz	2700Hz 500Hz	All modes - including Satellite downlinks Telegraphy (including EME CW) 144.050 MHz Telegraphy Centre of Activity 144.100 MHz Random MS telegraphy calling (Note 1)
144.100-144.150	500Hz	Telegraphy and MGM EME MGM activity
144.150-144.400	2700Hz	Telegraphy, MGM and SSB 144.250 MHz GB2RS news broadcast and slow Morse 144.260 MHz See Note 10 144.300 MHz SSB Centre of Activity 144.370 MHz MGM MS calling
144.400-144.490		Propagation Beacons only
144.490-144.500		Beacon guard band 144.491-144.493 MHz Personal Weak Signal MGM Beacons (BW: 500 Hz max)
144.500-144.794	12 kHz	All Modes (Note-8) 144.500 MHz Image Modes (SSTV, Fax etc) 144.600 MHz Data Centre of Activity (MGM, RTTY etc) 144.6125 MHz UK Digital Voice (DV) calling (Note 9) 144.625-144.675 MHz See Note 10 144.750 MHz ATV Talk-back 144.775-144.794 MHz See Note 10
144.794-144.990	12 kHz	MGM / Digital Communications 144.800-144.9875 MHz Digital modes (including unattended) 144.8000 MHz Unconnected nets - APRS, UView etc (Note 14) 144.8125 MHz DV Internet voice gateway (IARU common channel) 144.8250 MHz DV Internet voice gateway (IARU common channel) 144.8375 MHz DV Internet voice gateway (IARU common channel) 144.8500 MHz DV Internet voice gateway (IARU common channel) 144.8625 MHz DV Internet voice gateway (IARU common channel) 144.8750 - 144.9125 MHz - Internet Gateways 144.9250 MHz Digital usage 144.9375 MHz Digital usage 144.9500 MHz Digital usage 144.9625 MHz FM Internet voice gateway 144.9750, 144.9875 MHz Low power / Adhoc repeater inputs (Note 11)
144.990-145.1935	12 kHz	FM/DV RV48 - RV63 Repeater input exclusive (Note 2) (Note 5)
145.200	12 kHz	FM/DV Space communications (e.g. I.S.S.) - Earth-to-Space 145.2000 MHz (Note 4) & (Note 10)
145.200-145.5935	12 kHz	FM/DV V16-V45 FM/DV simplex (Note 3) (Note 5) (Note-6) 145.2125 MHz FM Internet voice gateway 145.2250 MHz Internet gateways - and See Note 10 145.2375 MHz FM Internet voice gateway (IARU common channel) 145.2500 MHz Used for slow Morse transmissions 145.2625 MHz FM Internet voice gateway 145.2875 MHz FM Internet voice gateway (IARU common channel) 145.3125 MHz FM Internet voice gateway 145.3375 MHz FM Internet voice gateway (IARU common channel) 145.5000 MHz FM calling (Note 12) 145.5250 MHz Used for GB2RS news broadcast. 145.5500 MHz Used for rally/exhibition talk-in 145.5750, 145.5875 MHz Low power / Adhoc repeater outputs (Note 11)
145.5935-145.7935	12 kHz	FM/DV RV48 - RV63 Repeater output (Note 2)
145.800	12 kHz	FM/DV Space communications (e.g. I.S.S.) - Space-Earth
145.806-146.000	12 kHz	All Modes - Satellite exclusive
Note 1: Meteor scatter operation can take place up to 26kHz higher than the reference frequency. Note 2: 12.5kHz channels numbered RV48-RV63. RV48 input = 145.000 MHz, output=145.600 MHz. Note 3: 12.5kHz simplex channels numbered V16-V45. V16=145.200 MHz. Note 4: Emergency Communications Groups utilising this frequency should take steps to avoid interference to ISS operations in non-emergency situations. Note 5: Embedded data traffic is allowed with digital voice (DV) Note 6: Simplex use only - no DV gateways Note 7: not used Note 8: Amplitude Modulation (AM) is acceptable within the All Modes segment. AM usage is typically found on 144.550MHz. Users should consider adjacent channel activity when selecting operating frequencies Note 9: In other countries IARU Region-1 recommend 145.375 MHz Note 10: May be used for Emergency Communications and Community Events Note 11: Ad-hoc Low power repeaters, 5W erp max Note 12: DV users are asked not to use this channel, and use 144.6125 MHz for calling. Note 13: not used Note 14: 144.800 use should be NBFM to avoid interference to 144.8125 DV Gateways LICENCE NOTES: Amateur Service and Amateur Satellite Service - Primary User. Note specific conditions apply within 50 km of TA 012869 (Scarborough)		

RSGB Band Plan (effective from 1st January 2018)

Access to this band requires an appropriate NoV, which is available to Full Licensees only

Note that the current NoVs last for up to one year prior to expiry on 31st October

For further information see the 146-147 MHz FAQ or contact vhf.manager@rgsb.org.uk

146-147 MHz (2m extension)	Necessary Bandwidth	UK Usage
146.000-146.900 MHz	500kHz	Wideband Digital Modes (High speed data , DATV etc) 146.500 MHz Centre frequency for wideband modes (Note 1)
146.900-147.000	12kHz	Narrowband Digital Modes including Digital Voice 146.9000 146.9125 146.9250 146.9375 Not available in/near Scotland (see Licence Notes & NoV terms) 146.9500 146.9625 146.9750 146.9875
Note-1: Users of wideband modes must ensure their spectral emissions are contained within the band limits LICENCE NOTES: Full Licensees only, with NoV, 50W erp max - not available in the Isle of Man or Channel Isles Note that additional restrictions on geographic location, antenna height and upper frequency limit are specified by the NoV terms It should be emphasised that this band is UK-specific and is available on a non-interference basis to existing services. Upper Band limit 147.000 MHz (or 146.93750 where applicable) are absolute limits and not centre frequencies The absolute band frequency limit in or within 40km of Scotland is 146.93750 MHz - see NoV schedule		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

RSGB Band Plan (effective from 1st January 2025)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

430 MHz (70cm) IARU Recommendation	Necessary Bandwidth	UK Usage
430.0000-431.9810 MHz All modes		430.0125-430.1000 MHz FM Internet voice gateways (Notes 7, 8) 430.1250-430.1375 MHz UK DV 9 MHz split repeaters - Inputs - (Note-10) 430.250-430.300 MHz UK DV 9 MHz reverse-split repeaters - Outputs 430.400-430.775 MHz UK DV 9 MHz split repeaters - Inputs 430.7875 MHz UR63 UK Reverse 7.6 MHz split repeater - Input 430.8000 MHz 7.6 MHz Talkthrough (Note 10) 430.8125-430.9750 MHz RU65-RU78 7.6 MHz split repeaters – outputs See licence exclusion note; 431-432 MHz 430.9900-431.9000 MHz Digital Communications 431.0250-431.2500 MHz DV Internet voice gateways (Note 8)
432.0000-432.4 000 All narrowband modes	2700 Hz	432.2000 MHz CW/SSB centre of activity 432.3500 MHz Microwave talkback (Europe)
432.4000-432.4900	500 Hz	Propagation Beacons only 432.491-432.493 MHz Personal Weak Signal MGM Beacons (BW: 500 Hz max)
432.5000-432.9940 All modes Non-channelised	12 kHz (Note 11)	432.5000 MHz Narrow band SSTV activity centre 432.6250-432.6750 MHz Digital communications 432.7750 MHz 1.6 MHz Talkthrough - Base TX (Note 10)
432.9940-433.3810 FM repeater outputs in UK only (Note 1)	12 kHz (Note 11)	433.0000-433.3750 MHz (RB0-RB15) RU240-RU270... and RBW0-RBW30 5 MHz split repeater outputs FM/DV repeater outputs in UK only
433.3940-433.5810 FM/DV (Notes 12, 13) Simplex Channels	12kHz (Note 11)	433.4000 MHz U272; IARU Region 1 SSTV (FM/AFSK) 433.4250 MHz U274 433.4500 MHz U276 (Note 5) 433.4750 MHz U278 433.5000 MHz U280 FM Calling channel 433.5250 MHz U282 433.5500 MHz U284 Used for Rally/Exhibition talk-in 433.5750 MHz U286
433.6000-434.0000 All modes 433.800 MHz for APRS where 144.800 MHz cannot be used.		433.6250-433.6750 MHz Digital communications 433.7000-433.7750 MHz (Note 10) 433.8000-434.2500 MHz Digital communications & Experiments (Note 3)
434.000-434.5940	12 kHz (Note 11)	434.0000 Low Power Hot-Spot usage (Note 4) 433.9500-434.0500 MHz Internet voice gateways (Note 8) 434.3750 MHz 1.6 MHz Talkthrough - Mobile TX (Note 10) 434.4750-434.5250 MHz DV Internet voice gateways (Note 8)
434.5940-434.9810 FM repeater inputs in UK	12 kHz (Note 11)	434.6000-434.9750 MHz (RB0-RB15) RU240-RU270 FM/DV repeater inputs in UK only (Note 12).
435.0000-436.0000 436.0000-438.0000		Satellites only Satellites and Experimental DATV/Data 437.0000 Experimental DATV/Data Centre of Activity (Note 14)
438.0000-440.0000		438.0000-438.3750 RBW00-RBW30 5 MHz split repeaters - inputs 438.0250-438.1750 MHz IARU Region 1 Digital communications
All modes		438.2000-439.4250 MHz (Note 1) 438.4000 MHz 7.6 MHz Talkthrough (Note 10) 438.4125-438.5750 MHz RU65-RU78 7.6MHz split repeaters – inputs 438.6125 MHz UK DV calling (Note 12) (Note 13) 438.8000 Low Power Hot-Spot usage (Note 4) 438.3875 MHz UR63 Reverse 7.6 MHz split repeaters output 439.1250-439.1375 MHz UK DV 9 MHz split repeaters - Outputs (Note-10) 439.250-439.300 MHz UK DV 9 MHz reverse-split repeaters - Inputs
		439.6000-440.0000 MHz Digital communications 439.400-439.775 MHz UK DV 9 MHz split repeaters - Outputs 439.900 - 439.9875 MHz Digital Communications including Low Power Lora Gateways; Pagers etc (Note-9)
Note 1: UK Repeaters in this band are based on 1.6, 5.0, 7.6 and 9MHz frequency splits and 12kHz BW to support 12.5kHz spacing. European systems may be different or reverse of our splits - See RSGB and ETCC websites for further information. Note 2: 430-440 MHz FM/DV maximum bandwidths are 12.5 or 25 kHz as appropriate Note 3: Digital Experiments include adhoc new and/or wider bandwidth modes such as Lora etc - also see Note 9 re 439.9MHz Note 4: Hot Spots - 438.775 and 438.7875 MHz are also options if preferred channels above are not available Note 5: In other countries IARU Region-1 recommend 433.450 MHz for DV calling Note 7: Users must accept interference from repeater output channels in France and the Netherlands at 430.025-430.575 MHz. Users with sites that allow propagation to other countries (notably France and the Netherlands) must survey the proposed frequency before use to ensure that they will not cause interference to users in those countries. Note 8: All Internet voice gateways: 12.5kHz channels, maximum deviation +2.4kHz, maximum ERP 5W (7 dBW), Note 9: Coordinated usage includes - Low-power Lora 125kHz Max BW at 439.9125 MHz; POCSAG Pagers at 439.9875MHz Note 10: May be used for Emergency Communications and Community Events Note 11: IARU Region 1 recommended maximum bandwidths are 12kHz to support 12.5kHz channel spacing Note 12: Embedded data traffic is allowed with digital voice (DV) Note 13: Simplex use only - no DV gateways Note 14: QPSK 2 Mega-symbols/second maximum recommended LICENCE NOTES: Amateur Service: Secondary User. Amateur Satellite Service: 435-438MHz: Secondary User Note specific conditions within 430-440MHz Exclusion: 431-432 MHz not available within 100km radius of Charing Cross, London. Power Restriction: 430-432 MHz is 40W ERP maximum		

RSGB Band Plan (effective from 1st January 2024)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on on frequencies above 430 MHz.

1.3 GHz (23cm)	Necessary Bandwidth	UK Usage
1240.000-1240.500	2700Hz	Alternative narrowband segment - see Note 7 1240.00-1240.750 MHz
1240.500-1240.750		Alternative Propagation Beacon Segment
1240.750-1241.000	20kHz	FM/DV Repeater Inputs
1241.000-1241.750 All modes	150 kHz	DD High Speed Digital Data - 5 x 150kHz channels 1241.075, 1241.225, 1241.375, 1241.525, 1241.675 MHz (+/- 75 kHz)
1241.750-1242.000 All modes	20kHz	25 kHz Channels available for FM/DV use 1241.775-1241.975 MHz
1242.000-1249.000 ATV		TV Repeaters (Note 9) New DATV repeater inputs (Note-10) Original ATV repeater inputs: 1248, 1249
1249.000-1249.250	20kHz	FM/DV Repeater Outputs, 25kHz channels (Note 9) 1249.025-1249.225 MHz
1250.00		In order to prevent interference to Primary Users, caution must be exercised prior to using 1250-1290MHz in the UK
1,260.000-1,270.000 Satellites		Amateur Satellite Service - Earth to Space uplinks only
1290.00		
1290.994-1291.481	20 kHz	FM/DV Repeater Inputs (Note-5) 1291.000-1291.375 MHz (RM0-RM15) 25 kHz spacing
1291.494-1296.000 All modes		All Modes
1296.000-1296.150 Telegraphy, MGM	500 Hz	Preferred narrowband segment 1296.000-1296.025 MHz Moonbounce
1296.150-1296.800 Telegraphy, SSB and MGM (Note 1)	2700 Hz	1296.200 MHz Narrow band centre of activity 1296.400-1296.600 MHz Linear transponder input 1296.500 MHz Image Mode Centre of Activity (SSTV, Fax etc) 1296.600 MHz Narrowband Data Centre of Activity (MGM, RTTY etc) 1296.600-1296.700 MHz Linear transponder output
		1296.741-1296.743 MHz Personal Weak Signal MGM Beacons
1296.800-1296.994 Beacons exclusive		1296.750-1296.800 MHz Local Beacons, 10W ERP max 1296.800-1296.990 MHz Propagation Beacons only
1296.994-1297.481	20 kHz	FM/DV Repeater Outputs (Note-5) 1297.000-1297.375 MHz (RM0-RM15)
1297.494-1297.981 FM/DV simplex (Notes 2, 5, 6)	20 kHz	FM/DV Simplex (Note-5)(Note-6) 25 kHz spacing 1297.500-1297.750 MHz (SM20-SM30) 1297.725 MHz Digital Voice (DV) Calling (IARU recommended) 1297.900-1297.975 MHz FM Internet voice gateways (IARU common channels, 25kHz)
1298.000-1299.000 All modes	20 kHz	All Modes General mixed analogue or digital use in channels 1298.025-1298.975 MHz (RS1-RS39)
1299.000-1299.750 All modes	150 kHz	DD High Speed Digital Data - 5 x 150kHz channels 1299.075, 1299.225, 1299.375, 1299.525, 1299.675 MHz (+/- 75 kHz)
1299.750-1300.000 All modes	20 kHz	25 kHz Channels available for FM/DV use 1299.775-1299.975 MHz
1300.000-1325.000 ATV		TV repeaters (UK only) (Note 9) New DATV repeater outputs (Note-10) Original ATV repeater outputs: 1308.0, 1310.0, 1311.5, 1312.0, 1316.0, 1318.5 MHz
Note 1: Local traffic using narrow band modes should operate between 1296.500-1296.800 MHz during contests and band openings. Note 2: Stations in countries that do not have access to 1298-1300 MHz may also use the FM simplex segment for digital communications. Note 5: Embedded data traffic is allowed with digital voice (DV) Note 6: Simplex use only - no DV gateways Note 7: 1240.000-1240.750 has been designated by IARU as an alternative centre for narrowband activity and beacons. Operations in this range should be on a flexible basis to enable coordinated activation of this alternate usage Note 8: The band 1240-1300MHz is subject to major replanning. Contact the Microwave Manager for further information Note 9: Repeaters and Migration to DATV, inc option for new DATV simplex are subject to further development and coordination Note-10: QPSK 4 Mega-symbols/second maximum recommended LICENCE NOTES: Amateur Service: Secondary User: Amateur Satellite Service: 1,260-1,270 MHz Secondary User Earth to Space only: Note specific conditions within 1240-1325MHz and within 50km of SS206127 (Bude), SE202577 (Harrogate), or in Northern Ireland.		

RSGB Band Plan (effective from 1st January 2018)

Access to this band requires an appropriate NoV, which is available to Full Licensees only

Please note that the current NoVs last for up to three years prior to expiry

For further information see the RSGB Website

2300-2302 MHz	Necessary Bandwidth	UK Usage
2300.000-2300.400	2.7 kHz	Narrowband Modes (including CW SSB, MGM) 2300.350-2300.400 Attended Beacons
2300.400-2301.800	500 kHz	Wideband Modes (NBFM, DV, Data , DATV etc) - Note-1 Note-2 for centre frequency recommendations
2301.800-2302.000	2.7kHz	Narrowband Modes (including CW SSB, MGM) EME Usage
Note-1: Users of wideband modes must ensure their spectral emissions are contained within the band limits Note-2: Recommended centre frequencies: DV/NBFM Voice etc 2300.500 MHz, Wideband Data/DATV - 2301.100 MHz LICENCE NOTES: Full Licensees only, with NoV, 400W max - not available in the Isle of Man Note that additional restrictions on usage are specified by the NoV terms It should be emphasised that this is UK-specific and is available on a non-interference basis to existing services.		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

RSGB Band Plan (effective from 1st January 2024)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

2.3 GHz (13cm) IARU Recommendation	Necessary Bandwidth	UK Usage
2,310.000-2,320.000 MHz Sub-regional (National band plans)	200 kHz	2,310.000-2,310.500 MHz Repeater links 2,311.000-2,315.000 MHz High speed data
2,320.000-2,320.800	2.7 kHz	Preferred Narrowband Segment 2,320.000-2,320.025 MHz Moonbounce 2,320.200 MHz SSB centre of activity 2,320.750-2,320.800 MHz Local Beacons, 10W erp max
2,320.800-2,321.000 Beacons exclusive		2,320.800-2,320.990 MHz Propagation Beacons only
2,321.000-2,322.000	20 kHz	FM/DV - see also Note 1
2,322.000-2,350.000		Wideband Modes , including data, ATV
2,390.000-2,400.000		All modes
2,400.000-2,450.000 Satellites		2,435.000 MHz ATV repeater outputs 2,440.000 MHz ATV repeater outputs
Note 1: Stations in countries which do not have access to the all modes section 2,322-2,400 MHz, may use the segment 2,321-2,322 MHz for data transmission. Note 2: Stations in countries that do not have access to the narrow band segment 2,320-2,322 MHz, use the alternative narrow band segments 2,304-2,306 MHz, 2,308-2,310 MHz and 2400-2402 MHz Note 3: The segment 2,433-2,443 MHz may be used for ATV if no satellite is using the segment. LICENCE NOTES: Amateur Service - Secondary User: <i>Users must accept interference from ISM users.</i> Amateur Satellite Service: 2,400-2,450 MHz - Secondary User: <i>Users must accept interference from ISM users</i> Operation in 2310-2350 and 2390-2400 MHz are subject to specific conditions and guidance Note specific conditions apply within 50km of SS206127 (Bude) or SE202577 (Harrogate). ISM = Industrial, scientific and medical.		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2021)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

3.4 GHz (9cm) IARU Recommendation	Necessary Bandwidth	UK Usage
3,400.000-3,400.800 MHz	2.7 kHz	Narrowband Modes (including CW SSB, MGM, EME) 3,400.100 MHz Centre of activity (Note 1) 3,400.750-3,400.800 MHz Local Beacons, 10W erp max
3,400.800-3,400.995 Propagation Beacons		3,400.800-3,400.995 MHz Propagation Beacons only
3,400.000-3,401.000	200 kHz	3,401.000-3,402.000 MHz Data, Remote control
3,402.000-3,410.000 All modes (Notes 2, 3)		Wideband Modes , including DATV Repeater Outputs
Note 1: EME has migrated from 3456 MHz to 3400 MHz to promote harmonised usage and activity Note 2: Stations in many European countries have access to 3400-3410 MHz as permitted by the CEPT ECA Table Note 3: Amateur Satellite downlinks planned LICENCE NOTES: Amateur Service - Secondary User - Subject to specific conditions and guidance		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2024)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on on frequencies above 430 MHz.

5.7 GHz (6cm) IARU Recommendation	Necessary Bandwidth	UK Usage
5,650.000-5,668.000 MHz Satellite uplinks	2.7kHz	All Modes Amateur Satellite Service - Earth to Space only
5,668.000-5,670.000		5,668.200 MHz Alternative narrowband centre
5,670.000-5,680.000		All Modes
5,755.000-5,760.000		All Modes
5,760.000-5,762.000	2.7kHz	Narrowband Modes (including CW, SSB, MGM, EME) 5,760.100 MHz Preferred centre of activity
		5,760.750-5,760.800 MHz Local Beacons, 10W erp max
5760.800-5760.995		5,760.800-5,760.995 MHz Propagation Beacons only
Propagation Beacons		
5,762.000-5,765.000		All Modes
5,820.000-5,830.000		All Modes
5,830.000-5,850.000 Satellite downlinks		All Modes Amateur Satellite Service - Space to Earth only
LICENCE NOTES: Amateur Service: 5,650-5,680 MHz - Secondary User. 5,755-5,765 and 5,820-5,850 MHz - Secondary User: <i>Users must accept interference from ISM users.</i> Amateur Satellite Service: 5,650-5,670 MHz and 5,830-5,850 MHz Secondary User: <i>Users must accept interference from ISM users.</i> Note specific conditions apply within 50km of SS206127 (Bude) or SE202577 (Harrogate). <i>ISM = Industrial, scientific and medical</i>		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2024)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on on frequencies above 430 MHz.

10 GHz (3cm) IARU Recommendation	Necessary Bandwidth	UK Usage
10,000.000-10,125.000 MHz All modes		Note-4 10,065 MHz ATV Repeater Outputs
10,225.000-10,250.000 All modes		10,240 MHz ATV Repeaters
10,250.000-10,350.000 Digital modes		
10,350.000-10,368.000 All modes		10,352.5-10,368 MHz Wideband modes (Note-2)
10,368.000-10,370.000 Narrowband telegraphy EME/SSB	2.7 kHz	10,368-10,370 MHz Narrowband modes (Note-3) 10,368.1 MHz Centre of activity
10,368.800-10,368.995 Propagation Beacons		10,368.750-10,368.800 MHz Local Beacons, 10W erp max 10,368.800-10,368.995 MHz Propagation Beacons only
10,370.000-10,450.000 All modes		10,371 MHz Voice repeaters RX 10,425 MHz ATV Repeaters
10,450.000-10,475.000 All modes and satellites		10,400-10,475 MHz Unattended operation 10,450-10,452 MHz Alternative narrowband segment (Note-3) 10,471 MHz Voice repeaters TX
10,475.000-10,500.000 All modes and satellites		Amateur Satellite Service ONLY (Note-5)
Note 1: Deleted Note 2: Wideband FM is preferred between 10,350-10,400 MHz to encourage compatibility with narrowband systems Note 3: 10450 MHz is used as an alternative narrowband segment in countries where 10,368 MHz is not available Note 4: 10,000-10,125 MHz is subject to increased Primary User utilisation and restrictions Note 5: 10,475-10,500 MHz is allocated ONLY to the Amateur Satellite Service and NOT to the Amateur Service. LICENCE NOTES: Amateur Service - Secondary User. Foundation Licensees 1W max Amateur Satellite Service: 10,450-10,500 MHz - Secondary User. Note specific conditions apply within 50 km of SO916223 (Cheltenham), SS206127 (Bude), SK985640 (Waddington) and SE202577 (Harrogate).		

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2024)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on on frequencies above 430 MHz.

24 GHz (12mm) IARU Recommendation	UK Usage
24,000.000-24,050.000 MHz	
Satellites	24,025 MHz Preferred operating frequency wideband equipment 24,048.2 MHz Narrow band center of activity
	24,048.750-24,048.800 MHz Local Beacons, 10W erp max
24,048.800-24,048.995	24,048.800-24,048.995 MHz Propagation Beacons Only
Propagation Beacons	
24,050.000-24,250.000	
All modes	
LICENCE NOTES: Amateur Service: 24,000-24,050 MHz - Primary User: <i>Users must accept interference from ISM users.</i> 24,050-24,150 MHz Secondary User: <i>May only be used with the written permission of Ofcom.</i> <i>Users must accept interference from ISM users.</i> 24,150-24,250 MHz Secondary User: <i>Users must accept interference from ISM users.</i> Amateur Satellite Service: 24,000-24,050 MHz Primary User: <i>Users must accept interference from ISM users.</i> Note specific conditions apply within 50 km of SK985640 (Waddington) and SE202577 (Harrogate). <i>ISM = Industrial, scientific and medical</i>	

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2024)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on on frequencies above 430 MHz.

47 GHz (6mm) IARU Recommendation	UK Usage
47,000.000-47,200.000 MHz 47,088.000-47,090.000 narrow band segment	47,088.2 MHz Centre of narrowband activity 47,088.8-47,089.0 MHz Propagation Beacons only
LICENCE NOTES: Amateur Service and Amateur Satellite Service Primary User. Note specific conditions apply within 50 km of SK985640 (Waddington) and SE202577 (Harrogate).	

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2024)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

76 GHz (4mm) IARU Recommendation	UK Usage
75,500-76,000 MHz All modes (preferred)	75,976.200 MHz IARU Region 1 preferred centre of activity
76,000.000-77,500.000 All modes	
77,500-78,000 All modes (preferred)	
78,000-81,000 All modes	
LICENCE NOTES: 75,500-75,875 MHz Amateur Service and Amateur Satellite Service - Secondary User . 75,875-76,000 MHz Amateur Service and Amateur Satellite Service - Primary User . 76,000-77,500 MHz Amateur Service and Amateur Satellite Service - Secondary User . 77,500-78,000 MHz Amateur Service and Amateur Satellite Service - Primary User . 78,000-81,000 MHz Amateur service and Amateur Satellite Service - Secondary User . Note specific conditions apply within 50 km of SK985640 (Waddington) and SE202577 (Harrogate).	

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

Foundation and Intermediate Licence holders are advised to check their licences for the permitted power limits and conditions applicable to their class of licence.

RSGB Band Plan (effective from 1st January 2024)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

122 GHz (2.5mm) IARU Recommendation	UK Usage
122,250-122,251 MHz Narrowband modes	IARU Region-1 preferred centre of activity
122,251-123,000 MHz All modes	122,256 / 122,400 MHz - UK centre of activity
LICENCE NOTES: 122,250-123,000 MHz Amateur Service only - Secondary User . Note specific conditions apply within 50 km of SK985640 (Waddington) and SE202577 (Harrogate).	

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

RSGB Band Plan (effective from 1st January 2024)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on frequencies above 430 MHz.

134 GHz (2mm) IARU Recommendation	UK Usage
134,000-134,928 MHz All modes	134,256 / 134,400 MHz - UK centre of activity IARU Region-1 preferred centre of activity
134,928-134,930 Narrowband modes	
134,930 -136,000 All modes	
136,000 -141,000 All modes	
LICENCE NOTES: 134,000-136,000 MHz Amateur Service and Amateur Satellite Service - Primary User . 136,000-141,000 MHz Amateur Service and Amateur Satellite Service - Secondary User . Note specific conditions apply within 50 km of SK985640 (Waddington) and SE202577 (Harrogate).	

Notes to the Band Plan

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.

RSGB Band Plan (effective from 1st January 2024)

The following band plan is largely based on that agreed at IARU Region 1 General Conferences with some local differences on on frequencies above 430 MHz.

241 GHz (1.2mm) IARU Recommendation	UK Usage
241,000-248,000 MHz All modes	241,600 MHz +/-IF - UK centre of activity
248,000-248,001 MHz Narrowband modes	IARU Region-1 preferred centre of activity
248,001-250,000 MHz All modes	248,800 MHz +/-IF - UK centre of activity
LICENCE NOTES: 241,000-248,000 MHz Amateur Service and Amateur Satellite Service - Secondary User . 248,000-250,000 MHz Amateur Service and Amateur Satellite Service - Primary User . Note specific conditions apply within 50 km of SK985640 (Waddington) and SE202577 (Harrogate).	

Notes to the Band Plan

Note-1: Access to frequencies >275 GHz by Full Licensees is also possible by NoV

ITU-R Recommendation SM.328 (extract)

Necessary bandwidth: For a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions.

The use of Amplitude Modulation (AM) is acceptable in the all modes segments but users are asked to consider adjacent channel activity when selecting operating frequencies.